

# Spindle ball bearing HY S 6016 E TXM P4+

16.04.2024



## Components


|                              |                  |
|------------------------------|------------------|
| Bearing designation:         | HY S 6016 E TXM  |
| Bearing design:              | S                |
| Series / size:               | 6016             |
| Ball material:               | Ceramic          |
| Cage:                        | TXM              |
| Precision:                   | P4+              |
| Main dimensions [d x D x B]: | 80 x 125 x 22 mm |

## Load data

|                       |                             |
|-----------------------|-----------------------------|
| Static load capacity  | $C_{0r}$ : 53500 N          |
| Dynamic load capacity | $C_r$ : 57000 N             |
| Fatigue load limit    | $C_U$ : 1994 N              |
| Speed limit           | $n_{grease}$ : 13125 1/min  |
| Speed limit           | $n_{oil}$ : 17500 1/min     |
| Light preload         | L: 490 N                    |
| Axial rigidity        | $C_{ax}$ : 257 N/μm         |
| Medium preload        | M: 1470 N                   |
| Axial rigidity        | $C_{ax}$ : 389 N/μm         |
| Heavy preload         | S: 2930 N                   |
| Axial rigidity        | $C_{ax}$ : 513 N/μm         |
| Spring preload        | Ff: 3780 N (for $n_{max}$ ) |

## Geometrical Data

|                                          |                         |                                              |                           |
|------------------------------------------|-------------------------|----------------------------------------------|---------------------------|
| Bore diameter                            | d: 80 mm                | Oiling nozzle position                       | $d_T$ : 98.6 mm           |
| Outer diameter                           | D: 125 mm               | Pitch circle diameter                        | $d_m$ : 102.5 mm          |
| Width of single bearing                  | B: 22 mm                | Inner diameter of outer ring                 | $D_1$ : 110.7 mm          |
| Ball diameter                            | $D_w$ : 13.494 mm       | Undercut of associated component             | $r_{a \max}$ : 1 mm       |
| Number of balls                          | Z: 20                   | Undercut of associated component (open side) | $r_{b \max}$ : 0.6 mm     |
| Chamfer (min)                            | $r_{1,2 \min}$ : 1.1 mm | Abutment diameter inner ring                 | $d_{a,b \min}$ : 87.7 mm  |
| Chamfer (min), open side                 | $r_{3,4 \min}$ : 0.6 mm | Abutment diameter outer ring                 | $D_{a,b \max}$ : 118.7 mm |
| Outer diameter of inner ring             | $d_1$ : 94.3 mm         | Inner diameter of outer ring (open side)     | $D_2$ : 116.2 mm          |
| Outer diameter of inner ring (open side) | $d_2$ : -               | Bearing weight                               | m: 0.72 kg                |
|                                          |                         | Contact angle                                | Alpha 0: 25°              |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.