Spindle ball bearing SM 61920 C TXM P4+

28.03.2024



Components


Bearing designation:	SM 61920 C TXM
Bearing design:	SM
Series / size:	61920
Ball material:	Steel 100Cr6
Cage:	TXM
Precision:	P4+
Main dimensions [d x D x B]:	100 x 140 x 20 mm

Load data

Static load capacity	C_{0r}:	31500 N
Dynamic load capacity	C_r:	37500 N
Fatigue load limit	C_U:	1480 N
Speed limit	n_{grease}:	12375 1/min
Speed limit	n_{oil}:	16500 1/min
Light preload	L:	190 N
Axial rigidity	C_{ax}:	106 N/µm
Medium preload	M:	570 N
Axial rigidity	C_{ax}:	159 N/µm
Heavy preload	S:	1150 N
Axial rigidity	C_{ax}:	210 N/µm
Spring preload	Ff:	2070 N (for n_{max})

Geometrical Data

Bore diameter	d:	100 mm
Outer diameter	D:	140 mm
Width of single bearing	B:	20 mm
Ball diameter	D_w:	11.906 mm
Number of balls	Z:	25
Chamfer (min)	$r_{1,2\ min}$:	0.6 mm
Chamfer (min), open side	$r_{3,4\ min}$:	0.6 mm
Outer diameter of inner ring	d_1:	112.8 mm
Outer diameter of inner ring (open side)	d_2:	-
Oiling nozzle position	d_T:	116.5 mm
Pitch circle diameter	d_m:	120 mm
Inner diameter of outer ring	D_1:	127.2 mm
Undercut of associated component	$r_{a\ max}$:	0.6 mm
Undercut of associated component (open side)	$r_{b\ max}$:	0.6 mm
Abutment diameter inner ring	$d_{a,b\ min}$:	105.7 mm
Abutment diameter outer ring	$D_{a,b\ max}$:	135.2 mm
Inner diameter of outer ring (open side)	D_2:	132.1 mm
Bearing weight	m:	0.79 kg
Contact angle	Alpha 0:	19°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.