

Complete Freewheel Clutch Unit FP 442 Z





Item number 300680

Components

| | |
|-------------------------|------------------------------------|
| Freewheel clutch | Insert Element FE 400 Z |
| · Rings | Bearing steel, hardened and ground |
| Inner ring | Press fit |
| Outer ring | Press fit |
| · Ball bearings | integrated |
| · Roller bearing | integrated |

Key values

| | |
|----------------------------|------------|
| Ø Shaft d: | 30 mm |
| Ø Hub D: | 46 mm |
| Installed width W: | 27 mm |
| Torque T_{nom} : | 208 Nm |
| Number of sprags: | 40 |
| Speed n_{max} : | 4200 rpm |
| Weight: | 0.142 kg |
| Load capacity C_{dyn} : | 10247 N |
| Load capacity C_{stat} : | 10708 N |
| Operating temperature: | max. 140°C |



Lubrication

Oil or grease lubrication

Delivered with corrosion protection.
Operative grease filling on request.

Installation

Installation tolerances

Shaft h5; hub H6

Mating parts

Hardening and grinding of the mating parts is not necessary. Thoroughly clean (grease free) the mating parts in the vicinity of the freewheel clutch as well as the freewheel clutch's rings before making the press fit.

Bearing

The freewheel clutch includes ball and roller bearings. Additional external bearing support is not necessary.

Press fit pressure

Press fit pressure must not be applied to the balls.

Clamping direction

The arrow on the inner ring designates the inner ring's clamping direction.