


# Spindle ball bearing HY KH 61903 E TA P4+

09.05.2024



## Components


|                              |                            |
|------------------------------|----------------------------|
| Bearing designation:         | HY KH 61903 E TA           |
| Bearing design:              | KH                         |
| Series / size:               | 61903                      |
| Ball material:               | Ceramic                    |
| Cage:                        | TA                         |
| Seal:                        | 2RZ optional (with grease) |
| Precision:                   | P4+                        |
| Main dimensions [d x D x B]: | 17 x 30 x 7 mm             |

## Load data

|                       |                            |
|-----------------------|----------------------------|
| Static load capacity  | $C_{0r}$ : 990 N           |
| Dynamic load capacity | $C_r$ : 2060 N             |
| Fatigue load limit    | $C_U$ : 38 N               |
| Speed limit           | $n_{grease}$ : 75000 1/min |
| Speed limit           | $n_{oil}$ : 100000 1/min   |
| Light preload         | L: 17 N                    |
| Axial rigidity        | $C_{ax}$ : 39 N/ $\mu$ m   |
| Medium preload        | M: 50 N                    |
| Axial rigidity        | $C_{ax}$ : 57 N/ $\mu$ m   |
| Heavy preload         | S: 100 N                   |
| Axial rigidity        | $C_{ax}$ : 74 N/ $\mu$ m   |
| Spring preload        | Ff: 70 N (for $n_{max}$ )  |

## Geometrical Data

|                                          |                         |                                              |                          |
|------------------------------------------|-------------------------|----------------------------------------------|--------------------------|
| Bore diameter                            | d: 17 mm                | Oiling nozzle position                       | $d_T$ : 22.2 mm          |
| Outer diameter                           | D: 30 mm                | Pitch circle diameter                        | $d_m$ : 23.3 mm          |
| Width of single bearing                  | B: 7 mm                 | Inner diameter of outer ring                 | $D_1$ : 25.6 mm          |
| Ball diameter                            | $D_w$ : 2.778 mm        | Undercut of associated component             | $r_{a \max}$ : 0.3 mm    |
| Number of balls                          | Z: 18                   | Undercut of associated component (open side) | $r_{b \max}$ : 0.3 mm    |
| Chamfer (min)                            | $r_{1,2 \min}$ : 0.3 mm | Abutment diameter inner ring                 | $d_{a,b \min}$ : 18.7 mm |
| Chamfer (min), open side                 | $r_{3,4 \min}$ : 0.3 mm | Abutment diameter outer ring                 | $D_{a,b \max}$ : 28.6 mm |
| Outer diameter of inner ring             | $d_1$ : 21 mm           | Inner diameter of outer ring (open side)     | $D_2$ : 26.2 mm          |
| Outer diameter of inner ring (open side) | $d_2$ : 20.7 mm         | Bearing weight                               | m: 0.017 kg              |
|                                          |                         | Contact angle                                | Alpha 0: 25°             |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.