

Spindle ball bearing HY S 6207 E TA P4+

08.05.2024



Components


Bearing designation:	HY S 6207 E TA
Bearing design:	S
Series / size:	6207
Ball material:	Ceramic
Cage:	TA
Seal:	2RZ upon request
Precision:	P4+ (UP+ Upon request)
Main dimensions [d x D x B]:	35 x 72 x 17 mm

Load data

Static load capacity	C_{0r} : 22400 N
Dynamic load capacity	C_r : 33500 N
Fatigue load limit	C_U : 848 N
Speed limit	n_{grease} : 25500 1/min
Speed limit	n_{oil} : 34000 1/min
Light preload	L: 280 N
Axial rigidity	C_{ax} : 156 N/ μ m
Medium preload	M: 840 N
Axial rigidity	C_{ax} : 238 N/ μ m
Heavy preload	S: 1700 N
Axial rigidity	C_{ax} : 320 N/ μ m
Spring preload	Ff: 1610 N (for n_{max})

Geometrical Data

Bore diameter	d: 35 mm	Oiling nozzle position	d_f : 50.9 mm
Outer diameter	D: 72 mm	Pitch circle diameter	d_m : 53.5 mm
Width of single bearing	B: 17 mm	Inner diameter of outer ring	D_1 : 60.6 mm
Ball diameter	D_w : 11.112 mm	Undercut of associated component	$r_{a \max}$: 1 mm
Number of balls	Z: 13	Undercut of associated component (open side)	$r_{b \max}$: 0.6 mm
Chamfer (min)	$r_{1,2 \min}$: 1.1 mm	Abutment diameter inner ring	$d_{a,b \min}$: 41.9 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.6 mm	Abutment diameter outer ring	$D_{a,b \max}$: 66.7 mm
Outer diameter of inner ring	d_1 : 47.4 mm	Inner diameter of outer ring (open side)	D_2 : 64.8 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.245 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.