

# Spindle ball bearing S 6009 C TA P4+

09.05.2024



## Components


|                              |                            |
|------------------------------|----------------------------|
| Bearing designation:         | S 6009 C TA                |
| Bearing design:              | S                          |
| Series / size:               | 6009                       |
| Ball material:               | Steel 100Cr6               |
| Cage:                        | TA                         |
| Seal:                        | 2RZ optional (with grease) |
| Precision:                   | P4+ (UP+ Upon request)     |
| Main dimensions [d x D x B]: | 45 x 75 x 16 mm            |

## Load data

|                       |                             |
|-----------------------|-----------------------------|
| Static load capacity  | $C_{0r}$ : 22800 N          |
| Dynamic load capacity | $C_r$ : 27000 N             |
| Fatigue load limit    | $C_U$ : 1187 N              |
| Speed limit           | $n_{grease}$ : 21375 1/min  |
| Speed limit           | $n_{oil}$ : 28500 1/min     |
| Light preload         | L: 130 N                    |
| Axial rigidity        | $C_{ax}$ : 61 N/ $\mu$ m    |
| Medium preload        | M: 400 N                    |
| Axial rigidity        | $C_{ax}$ : 103 N/ $\mu$ m   |
| Heavy preload         | S: 800 N                    |
| Axial rigidity        | $C_{ax}$ : 147 N/ $\mu$ m   |
| Spring preload        | Ff: 1290 N (for $n_{max}$ ) |

## Geometrical Data

|                                          |                         |                                              |                          |
|------------------------------------------|-------------------------|----------------------------------------------|--------------------------|
| Bore diameter                            | d: 45 mm                | Oiling nozzle position                       | $d_f$ : 57.6 mm          |
| Outer diameter                           | D: 75 mm                | Pitch circle diameter                        | $d_m$ : 60 mm            |
| Width of single bearing                  | B: 16 mm                | Inner diameter of outer ring                 | $D_1$ : 65 mm            |
| Ball diameter                            | $D_w$ : 8.731 mm        | Undercut of associated component             | $r_{a \max}$ : 1 mm      |
| Number of balls                          | Z: 18                   | Undercut of associated component (open side) | $r_{b \max}$ : 0.6 mm    |
| Chamfer (min)                            | $r_{1,2 \min}$ : 1 mm   | Abutment diameter inner ring                 | $d_{a,b \min}$ : 50.4 mm |
| Chamfer (min), open side                 | $r_{3,4 \min}$ : 0.6 mm | Abutment diameter outer ring                 | $D_{a,b \max}$ : 70.5 mm |
| Outer diameter of inner ring             | $d_1$ : 54.7 mm         | Inner diameter of outer ring (open side)     | $D_2$ : 68.9 mm          |
| Outer diameter of inner ring (open side) | $d_2$ : -               | Bearing weight                               | m: 0.24 kg               |
|                                          |                         | Contact angle                                | Alpha 0: 15°             |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.