

# Spindle ball bearing HY S 6210 C TA P4+

08.05.2024



## Components


|                              |                        |
|------------------------------|------------------------|
| Bearing designation:         | HY S 6210 C TA         |
| Bearing design:              | S                      |
| Series / size:               | 6210                   |
| Ball material:               | Ceramic                |
| Cage:                        | TA                     |
| Seal:                        | 2RZ upon request       |
| Precision:                   | P4+ (UP+ Upon request) |
| Main dimensions [d x D x B]: | 50 x 90 x 20 mm        |

## Load data

|                       |                             |
|-----------------------|-----------------------------|
| Static load capacity  | $C_{0r}$ : 35500 N          |
| Dynamic load capacity | $C_r$ : 47500 N             |
| Fatigue load limit    | $C_U$ : 1346 N              |
| Speed limit           | $n_{grease}$ : 22500 1/min  |
| Speed limit           | $n_{oil}$ : 30000 1/min     |
| Light preload         | L: 240 N                    |
| Axial rigidity        | $C_{ax}$ : 82 N/ $\mu$ m    |
| Medium preload        | M: 720 N                    |
| Axial rigidity        | $C_{ax}$ : 135 N/ $\mu$ m   |
| Heavy preload         | S: 1440 N                   |
| Axial rigidity        | $C_{ax}$ : 192 N/ $\mu$ m   |
| Spring preload        | Ff: 1470 N (for $n_{max}$ ) |

## Geometrical Data

|                                          |                         |                                              |                          |
|------------------------------------------|-------------------------|----------------------------------------------|--------------------------|
| Bore diameter                            | d: 50 mm                | Oiling nozzle position                       | $d_T$ : 66.7 mm          |
| Outer diameter                           | D: 90 mm                | Pitch circle diameter                        | $d_m$ : 70 mm            |
| Width of single bearing                  | B: 20 mm                | Inner diameter of outer ring                 | $D_1$ : 76.9 mm          |
| Ball diameter                            | $D_w$ : 12.7 mm         | Undercut of associated component             | $r_{a \max}$ : 1 mm      |
| Number of balls                          | Z: 15                   | Undercut of associated component (open side) | $r_{b \max}$ : 0.6 mm    |
| Chamfer (min)                            | $r_{1,2 \min}$ : 1.1 mm | Abutment diameter inner ring                 | $d_{a,b \min}$ : 57.4 mm |
| Chamfer (min), open side                 | $r_{3,4 \min}$ : 0.6 mm | Abutment diameter outer ring                 | $D_{a,b \max}$ : 84.1 mm |
| Outer diameter of inner ring             | $d_1$ : 62.5 mm         | Inner diameter of outer ring (open side)     | $D_2$ : 82.9 mm          |
| Outer diameter of inner ring (open side) | $d_2$ : -               | Bearing weight                               | m: 0.39 kg               |
|                                          |                         | Contact angle                                | Alpha 0: 15°             |



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.