Spindle ball bearing HY KH 6016 E TA P4+

19.03.2024



Components


Bearing designation:	HY KH 6016 E TA
Bearing design:	KH
Series / size:	6016
Ball material:	Ceramic
Cage:	TA
Seal:	2RZ optional (with grease)
Precision:	P4+
Main dimensions [d x D x B]:	80 x 125 x 22 mm

Load data

Static load capacity	C_{0r}:	23600 N
Dynamic load capacity	C_r:	31000 N
Fatigue load limit	C_U:	892 N
Speed limit	n_{grease}:	17625 1/min
Speed limit	n_{oil}:	23500 1/min
Light preload	L:	260 N
Axial rigidity	C_{ax}:	182 N/µm
Medium preload	M:	790 N
Axial rigidity	C_{ax}:	270 N/µm
Heavy preload	S:	1580 N
Axial rigidity	C_{ax}:	348 N/µm
Spring preload	Ff:	1690 N (for n_{max})

Geometrical Data

Bore diameter	d:	80 mm
Outer diameter	D:	125 mm
Width of single bearing	B:	22 mm
Ball diameter	D_w:	11.112 mm
Number of balls	Z:	24
Chamfer (min)	$r_{1,2\ min}$:	1.1 mm
Chamfer (min), open side	$r_{3,4\ min}$:	0.6 mm
Outer diameter of inner ring	d_1:	94.3 mm
Outer diameter of inner ring (open side)	d_2:	92.6 mm
Oiling nozzle position	d_T:	97.7 mm
Pitch circle diameter	d_m:	100.9 mm
Inner diameter of outer ring	D_1:	107.5 mm
Undercut of associated component	$r_{a\ max}$:	1 mm
Undercut of associated component (open side)	$r_{b\ max}$:	0.6 mm
Abutment diameter inner ring	$d_{a,b\ min}$:	87 mm
Abutment diameter outer ring	$D_{a,b\ max}$:	119.2 mm
Inner diameter of outer ring (open side)	D_2:	112.2 mm
Bearing weight	m:	0.8 kg
Contact angle	Alpha 0:	25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.