

Spindle ball bearing S 61912 E TA P4+

08.05.2024



Components


Bearing designation:	S 61912 E TA
Bearing design:	S
Series / size:	61912
Ball material:	Steel 100Cr6
Cage:	TA
Seal:	2RZ upon request
Precision:	P4+
Main dimensions [d x D x B]:	60 x 85 x 13 mm

Load data

Static load capacity	C_{0r} : 18100 N
Dynamic load capacity	C_r : 18100 N
Fatigue load limit	C_U : 941 N
Speed limit	n_{grease} : 15000 1/min
Speed limit	n_{oil} : 20000 1/min
Light preload	L: 150 N
Axial rigidity	C_{ax} : 135 N/μm
Medium preload	M: 460 N
Axial rigidity	C_{ax} : 206 N/μm
Heavy preload	S: 920 N
Axial rigidity	C_{ax} : 273 N/μm
Spring preload	Ff: 1780 N (for n_{max})

Geometrical Data

Bore diameter	d: 60 mm	Oiling nozzle position	d_T : 70.4 mm
Outer diameter	D: 85 mm	Pitch circle diameter	d_m : 72.5 mm
Width of single bearing	B: 13 mm	Inner diameter of outer ring	D_1 : 76.9 mm
Ball diameter	D_w : 7.144 mm	Undercut of associated component	$r_{a \max}$: 1 mm
Number of balls	Z: 23	Undercut of associated component (open side)	$r_{b \max}$: 0.3 mm
Chamfer (min)	$r_{1,2 \min}$: 1 mm	Abutment diameter inner ring	$d_{a,b \min}$: 64.9 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.3 mm	Abutment diameter outer ring	$D_{a,b \max}$: 80.5 mm
Outer diameter of inner ring	d_1 : 68.1 mm	Inner diameter of outer ring (open side)	D_2 : 79.7 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.19 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.