Spindle ball bearing HY SM 6016 C TXM P4+

19.03.2024



Components


Bearing designation:	HY SM 6016 C TXM
Bearing design:	SM
Series / size:	6016
Ball material:	Ceramic
Cage:	TXM
Precision:	P4+
Main dimensions [d x D x B]:	80 x 125 x 22 mm

Load data

Static load capacity	C_{0r}:	30000 N
Dynamic load capacity	C_r:	43000 N
Fatigue load limit	C_U:	1112 N
Speed limit	n_{grease}:	18375 1/min
Speed limit	n_{oil}:	24500 1/min
Light preload	L:	220 N
Axial rigidity	C_{ax}:	95 N/µm
Medium preload	M:	650 N
Axial rigidity	C_{ax}:	143 N/µm
Heavy preload	S:	1300 N
Axial rigidity	C_{ax}:	190 N/µm
Spring preload	Ff:	1380 N (for n_{max})

Geometrical Data

Bore diameter	d:	80 mm
Outer diameter	D:	125 mm
Width of single bearing	B:	22 mm
Ball diameter	D_w:	13.494 mm
Number of balls	Z:	20
Chamfer (min)	$r_{1,2\ min}$:	1.1 mm
Chamfer (min), open side	$r_{3,4\ min}$:	0.6 mm
Outer diameter of inner ring	d_1:	94.3 mm
Outer diameter of inner ring (open side)	d_2:	-
Oiling nozzle position	d_T:	98.6 mm
Pitch circle diameter	d_m:	102.5 mm
Inner diameter of outer ring	D_1:	110.7 mm
Undercut of associated component	$r_{a\ max}$:	1 mm
Undercut of associated component (open side)	$r_{b\ max}$:	0.6 mm
Abutment diameter inner ring	$d_{a,b\ min}$:	87.7 mm
Abutment diameter outer ring	$D_{a,b\ max}$:	118.7 mm
Inner diameter of outer ring (open side)	D_2:	116.2 mm
Bearing weight	m:	0.72 kg
Contact angle	Alpha 0:	17°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.