

# Spindle ball bearings (HY)\* S 61902 E



## Precision class P4 / ABEC7

### Components

Bearing designation:	(HY)* S 61902 E
Bearing design:	S
Series / size:	61902
Ball material:	Steel 100Cr6
Ball material HY :	Ceramic Si3N4
Cage:	TA (TXM available upon request)
Precision:	P4 (HG, UP, P2 upon request)
Main dimensions [d x D x B]:	15 x 28 x 7 mm

### Technical data (Standard bearings)

Static load capacity $C_0$ :	2330
Dynamic load capacity C:	4300
Speed limit $n_{Fett}$ :	50250
Speed limit $n_{Oj}$ :	67000

### Technical data (Hybrid bearings)\*

Static load capacity $C_{0HY}$ :	1640
Dynamic load capacity $C_{HY}$ :	4300
Speed limit $n_{Fett}$ :	62812.5
Speed limit $n_{Oj}$ :	83750

### Pre-tension

Light (L):	35 N
Axial rigidity ( $C_{ax}$ ):	44 N/ $\mu$ m
Medium (M):	110 N
Axial rigidity ( $C_{ax}$ ):	68 N/ $\mu$ m
Heavy (S):	220 N
Axial rigidity ( $C_{ax}$ ):	89 N/ $\mu$ m
Spring preload (Ff):	160 N

The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.

\* All ball bearings are also available as hybrid ball bearings (HY).