

Spindle ball bearing S 61920 E TXM P4+

08.05.2024



Components


Bearing designation:	S 61920 E TXM
Bearing design:	S
Series / size:	61920
Ball material:	Steel 100Cr6
Cage:	TXM
Precision:	P4+
Main dimensions [d x D x B]:	100 x 140 x 20 mm

Load data

Static load capacity	C_{0r} : 54500 N
Dynamic load capacity	C_r : 48500 N
Fatigue load limit	C_U : 2589 N
Speed limit	n_{grease} : 9000 1/min
Speed limit	n_{oil} : 12000 1/min
Light preload	L: 410 N
Axial rigidity	C_{ax} : 238 N/ μ m
Medium preload	M: 1230 N
Axial rigidity	C_{ax} : 360 N/ μ m
Heavy preload	S: 2470 N
Axial rigidity	C_{ax} : 476 N/ μ m
Spring preload	Ff: 4910 N (for n_{max})

Geometrical Data

Bore diameter	d: 100 mm	Oiling nozzle position	d_T : 116.5 mm
Outer diameter	D: 140 mm	Pitch circle diameter	d_m : 120 mm
Width of single bearing	B: 20 mm	Inner diameter of outer ring	D_1 : 127.2 mm
Ball diameter	D_w : 11.906 mm	Undercut of associated component	$r_{a \max}$: 0.6 mm
Number of balls	Z: 25	Undercut of associated component (open side)	$r_{b \max}$: 0.6 mm
Chamfer (min)	$r_{1,2 \min}$: 0.6 mm	Abutment diameter inner ring	$d_{a,b \min}$: 105.7 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.6 mm	Abutment diameter outer ring	$D_{a,b \max}$: 135.2 mm
Outer diameter of inner ring	d_1 : 112.8 mm	Inner diameter of outer ring (open side)	D_2 : 132.1 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.79 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.