

Spindle ball bearing HY SM 608 C TXM P4+

08.05.2024



Components


Bearing designation:	HY SM 608 C TXM
Bearing design:	SM
Series / size:	608
Ball material:	Ceramic
Cage:	TXM
Precision:	P4+ (UP+ Upon request)
Main dimensions [d x D x B]:	8 x 22 x 7 mm

Load data

Static load capacity	C_{0r} : 950 N
Dynamic load capacity	C_r : 2700 N
Fatigue load limit	C_U : 36 N
Speed limit	n_{grease} : 127500 1/min
Speed limit	n_{oil} : 170000 1/min
Light preload	L: 13 N
Axial rigidity	C_{ax} : 11 N/ μ m
Medium preload	M: 40 N
Axial rigidity	C_{ax} : 17 N/ μ m
Heavy preload	S: 80 N
Axial rigidity	C_{ax} : 24 N/ μ m
Spring preload	Ff: 40 N (for n_{max})

Geometrical Data

Bore diameter	d: 8 mm	Oiling nozzle position	d_T : 13.4 mm
Outer diameter	D: 22 mm	Pitch circle diameter	d_m : 14.7 mm
Width of single bearing	B: 7 mm	Inner diameter of outer ring	D_1 : 17.6 mm
Ball diameter	D_w : 3.969 mm	Undercut of associated component	$r_{a \max}$: 0.3 mm
Number of balls	Z: 9	Undercut of associated component (open side)	$r_{b \max}$: 0.3 mm
Chamfer (min)	$r_{1,2 \min}$: 0.3 mm	Abutment diameter inner ring	$d_{a,b \min}$: 10.2 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.3 mm	Abutment diameter outer ring	$D_{a,b \max}$: 20.5 mm
Outer diameter of inner ring	d_1 : 11.8 mm	Inner diameter of outer ring (open side)	D_2 : 18.7 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.01 kg
		Contact angle	Alpha 0: 15°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.