


Spindle ball bearing KH 6008 C TXM P4+

08.05.2024



Components

Bearing designation:	KH 6008 C TXM
Bearing design:	KH
Series / size:	6008
Ball material:	Steel 100Cr6
Cage:	TXM
Seal:	2RZ optional (with grease)
Precision:	P4+
Main dimensions [d x D x B]:	40 x 68 x 15 mm

Load data

Static load capacity	C_{0r} : 6950 N
Dynamic load capacity	C_r : 10900 N
Fatigue load limit	C_U : 361 N
Speed limit	n_{grease} : 29250 1/min
Speed limit	n_{oil} : 39000 1/min
Light preload	L: 55 N
Axial rigidity	C_{ax} : 44 N/ μ m
Medium preload	M: 160 N
Axial rigidity	C_{ax} : 65 N/ μ m
Heavy preload	S: 330 N
Axial rigidity	C_{ax} : 88 N/ μ m
Spring preload	Ff: 450 N (for n_{max})

Geometrical Data

Bore diameter	d: 40 mm	Oiling nozzle position	d_T : 51.4 mm
Outer diameter	D: 68 mm	Pitch circle diameter	d_m : 53.3 mm
Width of single bearing	B: 15 mm	Inner diameter of outer ring	D_1 : 57.5 mm
Ball diameter	D_w : 6.35 mm	Undercut of associated component	$r_{a \max}$: 1 mm
Number of balls	Z: 22	Undercut of associated component (open side)	$r_{b \max}$: 0.6 mm
Chamfer (min)	$r_{1,2 \min}$: 1 mm	Abutment diameter inner ring	$d_{a,b \min}$: 44.7 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.6 mm	Abutment diameter outer ring	$D_{a,b \max}$: 64 mm
Outer diameter of inner ring	d_1 : 49.2 mm	Inner diameter of outer ring (open side)	D_2 : 59.8 mm
Outer diameter of inner ring (open side)	d_2 : 47.5 mm	Bearing weight	m: 0.195 kg
		Contact angle	Alpha 0: 17°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.