

Spindle ball bearing HY S 61909 E TXM P4+

08.05.2024



Components


Bearing designation:	HY S 61909 E TXM
Bearing design:	S
Series / size:	61909
Ball material:	Ceramic
Cage:	TXM
Precision:	P4+
Main dimensions [d x D x B]:	45 x 68 x 12 mm

Load data

Static load capacity	C_{0r} : 12500 N
Dynamic load capacity	C_r : 14300 N
Fatigue load limit	C_U : 472 N
Speed limit	n_{grease} : 24000 1/min
Speed limit	n_{oil} : 32000 1/min
Light preload	L: 120 N
Axial rigidity	C_{ax} : 125 N/μm
Medium preload	M: 360 N
Axial rigidity	C_{ax} : 190 N/μm
Heavy preload	S: 720 N
Axial rigidity	C_{ax} : 252 N/μm
Spring preload	Ff: 900 N (for n_{max})

Geometrical Data

Bore diameter	d: 45 mm	Oiling nozzle position	d_T : 54.5 mm
Outer diameter	D: 68 mm	Pitch circle diameter	d_m : 56.5 mm
Width of single bearing	B: 12 mm	Inner diameter of outer ring	D_1 : 60.7 mm
Ball diameter	D_w : 6.35 mm	Undercut of associated component	$r_{a \max}$: 0.6 mm
Number of balls	Z: 20	Undercut of associated component (open side)	$r_{b \max}$: 0.3 mm
Chamfer (min)	$r_{1,2 \min}$: 0.6 mm	Abutment diameter inner ring	$d_{a,b \min}$: 48.8 mm
Chamfer (min), open side	$r_{3,4 \min}$: 0.3 mm	Abutment diameter outer ring	$D_{a,b \max}$: 64.7 mm
Outer diameter of inner ring	d_1 : 52.3 mm	Inner diameter of outer ring (open side)	D_2 : 62.9 mm
Outer diameter of inner ring (open side)	d_2 : -	Bearing weight	m: 0.11 kg
		Contact angle	Alpha 0: 25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.