HSX 170 - 18000/34



TECHNICAL DATA



FIT HOLES WITH FLAT LAYOUT



ANGLED PLUG OPTION



The data currently provided on the internet apply. Further and detailed information is provided in the GMN 2508 catalogue.

Technical data			HSX 170 - 18000/34		
ø Spindle housing	A	[mm]	170		
Speed max.	n_{max}	[min^{-1}]	18000		
Bearing; front	W_1	[mm]	70		
Tool interface			D 36/68		
ø Flat layout	W	[mm]	68		
Static rigidity					
axial	C_{ax}	[N/µm]	135		
radial	C_{rad}	[N/µm]	262		
Motor realization			200 V	350 V	460 V
Frequency max.	f_{max}	[Hz]	600		
Converter voltage[1)]		[V]	200	350	460
Power	P_{S1}	[kW]	29		
Torque	M_{S1}	[Nm]	25,2		
... at speed	n	[min^{-1}]	11000		
Current	I_{S1}	[A]	117	67	51
Power	$P_{S6\text{-}60\%}$	[kW]	34		
Torque	$M_{S6\text{-}60\%}$	[Nm]	29,5		
... at speed	n	[min^{-1}]	11000		
Current	$I_{S6\text{-}60\%}$	[A]	137	78	59

Electrical connection			
Plug type	D350	MAC	MAC
Straight plug connection	+	+	+
Coil plug connector	o	o	o
Fixed cable XXm	o	o	o
Coolant feed through the shaft			
Low pressure (du)	-		
High-pressure (dh)	x		
Sensors			
Rotary encoder	x		
Speed sensor	+		
Housing			
Cylindrical housing	+		
Cylindrical housing with flange	o		
Block housing	x		
Air-tight seal	o		

[1)] Minimum required starting voltage for the frequency converter.

+ Standard
o Optional
x Upon request



Ordering information:
HSX 170 - 18000/34
R is for clockwise, L for counter-clockwise
+ Desired options

HSX 170 - 18000/34

Grinding quills

GMN produces grinding quills with high round and flat face accuracy for all available GMN grinding mandrel receivers.

FIG. 1: CEMENTED (KI)



FIG. 2: WITH ADJUSTMENT SCREW (PS)



FIG. 3: FOR GRINDING WHEELS ON THREADED PIN (PL)*



FITTING HOLE FOR FIG. 2 AND 3



d_1	M	L_5	L_6
4	M3	5	8
6	M5	7	11
8	M6	9	12
10	M8	12	14
13	M12	13	17

Interface	K [mm]	H [mm]	Wheel E x F [mm]	G [mm]	Grinding wheel attachment	H_O [mm]
D 36/68	32	63	50 x 40	20	MU	15
	40	80	63 x 40	25	MU	
	56	125	100 x 40	36	MU	

Ordering information:
[Mandrel ø K] x [Mandrel length H] - [Grinding wheels ø G] x [Grinding wheel width F] [Interface] [Mandrel fixation]
Example: Grinding quill 16 x 40 - 10 x 25 D16/28 PS

Lubrication system

The electronically controlled PRELUB lubrication unit is optimally adapted to the oil-air lubricated GMN spindles and guarantees a long service life.

Cooling system

GMN cooling units ensure precisely adjustable temperature and quantity delivery of the coolant and achieve consistently low operating temperatures.

Cable and plug

Ready-made cables with B048, B049, GA, MAC, D500 and STK plugs are available on request. For the spindle/converter connection, GMN supplies UL/CSA approved electrical cables suitable for use in drag chains.