# Spindle ball bearing 60 6006 0 T9H P4

24.11.2026

## Components

| | |
|---|---|
| Bearing designation: | 60 6006 0 T9H |
| Bearing design: | 60 |
| Series / size: | 6006 |
| Ball material: | Steel 100Cr6 |
| Cage: | T9H |
| Seal: | 2Z auf Anfrage |
| Precision: | P4 (HG;UP;P2 Upon request) |
| Main dimensions [d x D x B]: | 30 x 55 x 13 mm |

## Load data

| | | |
|---|---|---|
| Static load capacity | $C_{0r}$: | 8400 N |
| Dynamic load capacity | $C_r$: | 13200 N |
| Fatigue load limit | $C_U$: | 0 N |
| Speed limit | $n_{grease}$: | 17400 1/min |
| Speed limit | $n_{oil}$: | 23200 1/min |
| Light preload | L: | 0 N |
| Axial rigidity | $C_{ax}$: | 0 N/µm |
| Medium preload | M: | 0 N |
| Axial rigidity | $C_{ax}$: | 0 N/µm |
| Heavy preload | S: | 0 N |
| Axial rigidity | $C_{ax}$: | 0 N/µm |
| Spring preload | Ff: | 0 N (for $n_{max}$) |

## Geometrical Data

| | | |
|---|---|---|
| Bore diameter | d: | 30 mm |
| Outer diameter | D: | 55 mm |
| Width of single bearing | B: | 13 mm |
| Ball diameter | $D_w$: | 7.144 mm |
| Number of balls | Z: | 11 |
| Chamfer (min) | $r_{1,2\ min}$: | 1 mm |
| Chamfer (min), open side | $r_{3,4\ min}$: | - |
| Outer diameter of inner ring | $d_1$: | 38.1 mm |
| Outer diameter of inner ring (open side) | $d_2$: | - |
| Oiling nozzle position | $d_T$: | - |
| Pitch circle diameter | $d_m$: | 42.5 mm |
| Inner diameter of outer ring | $D_1$: | 47 mm |
| Undercut of associated component | $r_{a\ max}$: | 1 mm |
| Undercut of associated component (open side) | $r_{b\ max}$: | - |
| Abutment diameter inner ring | $d_{a,b\ min}$: | 36 mm |
| Abutment diameter outer ring | $D_{a,b\ max}$: | 49 mm |
| Inner diameter of outer ring (open side) | $D_2$: | - |
| Bearing weight | m: | 0.128 kg |
| Contact angle | Alpha 0: | - |

The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.