Spindle ball bearing S 61808 E TA P4+

24.11.2026



Components

Bearing designation:	S 61808 E TA
Bearing design:	S
Series / size:	61808
Ball material:	Steel 100Cr6
Cage:	TA
Precision:	P4+
Main dimensions [d x D x B]:	40 x 52 x 7 mm

Load data

Static load capacity	C_{0r}:	3750 N
Dynamic load capacity	C_r:	3800 N
Fatigue load limit	C_U:	194 N
Speed limit	n_{grease}:	24000 1/min
Speed limit	n_{oil}:	32000 1/min
Light preload	L:	30 N
Axial rigidity	C_{ax}:	61 N/µm
Medium preload	M:	100 N
Axial rigidity	C_{ax}:	96 N/µm
Heavy preload	S:	190 N
Axial rigidity	C_{ax}:	123 N/µm
Spring preload	Ff:	370 N (for n_{max})

Geometrical Data

Bore diameter	d:	40 mm
Outer diameter	D:	52 mm
Width of single bearing	B:	7 mm
Ball diameter	D_w:	3.175 mm
Number of balls	Z:	26
Chamfer (min)	$r_{1,2\ min}$:	0.3 mm
Chamfer (min), open side	$r_{3,4\ min}$:	0.3 mm
Outer diameter of inner ring	d_1:	43.9 mm
Outer diameter of inner ring (open side)	d_2:	-
Oiling nozzle position	d_T:	44.9 mm
Pitch circle diameter	d_m:	46 mm
Inner diameter of outer ring	D_1:	48.1 mm
Undercut of associated component	$r_{a\ max}$:	0.3 mm
Undercut of associated component (open side)	$r_{b\ max}$:	0.3 mm
Abutment diameter inner ring	$d_{a,b\ min}$:	41.6 mm
Abutment diameter outer ring	$D_{a,b\ max}$:	50.5 mm
Inner diameter of outer ring (open side)	D_2:	49.2 mm
Bearing weight	m:	0.03 kg
Contact angle	Alpha 0:	25°



The given speed limits apply to individual bearings with spring preload. Correction factors must be considered for all properties which deviate from this.