
TSP 60 x 200



Technical data




Maximum speed n_{max} [min-1]* for bearing types:

Steel (steel)	30000
Hybrid (optional)	35000


* without tool

Ordering information: TSP 60 x 200 R is for clockwise, L for counter-clockwise


ROTATION (CW.)



ROTATION (CCW.)




Tool interface



Tool interface: fitting bores with flat contact face acc. to GMN precision standards


Pulley interface



Pulley interface: taper 1 : 7,5 nominal value, included angle acc. to GMN precision standards

Accessories


Pulleys



Interface	Dimensions [mm]		
	D	C	T
A 18	25	60	40
	32	60	40
	40	60	40
	100	60	40

Ordering information pulley: AX_1-X_2
X_1: Interface: 10/13/...
X_2: Figure from column D
Puller for pulley: AX_1/...


TSP Collet chuck



Interface	Dimensions [mm]				
	K	T	L	S	W
D 14/23	6	20	30	23	23

Ordering information collet chuck: D 14/23/(K)
(K) = Clamping diameter

TSP Grinding quill – semifinished



Ordering information semifinished: DX_1/X_2
X_1/X_2 : Interface 08/14/...

This data sheet reflects the state of information at the time of printing. Subject to technical changes. Information on possible options can be obtained from our catalogue which can be downloaded at www.gmn.de